

Welcome

Welcome to the new E-Stim Systems ElectroRing System.

Others may offer simple cock rings, we have created not just a single ElectroRing but a system that can function not only as cock rings but can also take your electro cock play experience to the next dimension with a more chastity like device, even to the extend of not being able to remove the ElectroRing System without tools.

Each ElectroRing has been created to work with our heavy duty 4mm connectors, perfectly designed for use with our low profile cables. We don't even force you to choose which side you connect the cable to - the socket connections are double sided.

You can use the E-Stim ElectroRings either as a single ring or as part of a Bipolar System.

Safety

DO NOT CONNECT ANY ELECTRICAL DEVICE TO ANY LOCATION ABOVE THE WAIST (ACROSS THE ARMS COUNTS AS ABOVE THE WAIST!), BUT ESPECIALLY DO NOT CONNECT ACROSS THE HEART, CHEST, NECK OR HEAD. DO NOT USE IF FITTED WITH A PACEMAKER ARE EPILEPTIC OR ARE OR MAYBE PREGNANT. REMEMBER YOU USE THIS DEVICE AT YOUR OWN RISK.

The ElectroRing System

The E-Stim Systems ElectroRing System is a bipolar set of rings separated from each other with an insulator giving bipolar sensations. Generally you have a larger ring behind the testicles and a smaller Ring 'locked' onto the penile shaft with two thumb screws, the Ring System is easy to use and highly effective.

Secure as you wish

If you want it more secure then use the Hex headed bolts instead of the Thumb screws, - that way your subject will find it highly difficult to remove without the correct tool.



How to fit the ElectroRing System

1. Using the supplied hex key screw the insulator block to the larger ring. Make sure the screw heads fit into the recesses in the ring. Do not over tighten. This is the ring that will fit behind the testicles.
2. Now place the ring over the shaft and testicles and slip the testicles in one at a time, so the ring now sits at the base of the shaft.
3. Slide the second ring over the shaft, align the screw holes on the ring with the insulator block and then screw in the black headed screws. Do not over tighten and be careful not to trap any delicate skin when screwing it all together. If you are looking for something a little more secure, that will required a tool to remove, then use the smaller Allen headed screws.
4. Using an E-Stim Systems 4mm connection cable insert one plug into one ring, and the other plug on the other ring. DO NOT plug both plugs into the same ring.
5. Plug into your power box, don't forget to ensure the box is switched off.
6. Lastly, Make sure the levels are at zero and then switch your power box on. Gradually turn the levels up and enjoy!!!

If you experience sharpness or hotspots then consider using conductive gel to lubricate and smooth the sensation.

To Remove

1. Turn the outputs of the power box to zero, Switch the power box off and unplug the power cable.
2. Unscrew the black headed screws, or if you are using the more secure bolts, use the supplied hex key.
3. Slide off the front ring.
4. Lastly manoeuvre the testicles and shaft through the larger ring.

Using Single Rings

You can if you wish use a single ring as a more conventional cock ring, on in conjunction with another electrode as a second point of contact. In this situation all you need to do is to slip the ring on in the position you wish, and connect to an E-Stim Systems power box with a connection cable with a 4mm plug. If you are using a single ring, then ensure it does not touch anything else that is part of the circuit, or a short circuit may occur.

DO NOT connect two plugs into the same ElectroRing.

Cleaning

As with all of our insertable electrodes clean before and after use. Do not use caustic cleaning solutions, and always ensure the ElectroRings System and all the component parts are dry before storing. Use of bleach may cause the ElectroRings to discolour and is not recommended.